

Jumpers(Patchcords and Pigtailes) *Product Information*

Issue Date: 2006/05

FEATURES

- Low insertion loss
- High return loss
- Environmentally stable and reliable
- Precise dimension
- Excellent mechanical performance
- Wide band
- Stable performance
- Low polarization dependence
- Low attenuation error and high return loss
- Bellcore standard (GR-910-core) conformed



APPLICATIONS

- Telecommunication
- LAN(Local area network)
- FTTH(Fiber to the home)
- Fiber optic sensing
- Testing instrument
- CATV

SPECIFICATIONS

		PC	UPC	APC
Insertion Loss (dB)	SM	<0.20	<0.15	<0.20
	MM	<0.30	<0.20	<0.30
Return Loss (dB)		≥45	≥55	≥65
Operation temperature (°C)		-45 ~ +75		
Storage temperature (°C)		-55 ~ +85		

ORDERING INFORMATION

PA-SM-LL-C-N-1XX/XXX-1XX/XXX

- Output end connector type: FC/PC, SC/PC, ST/PC, etc.
- Input end connector type: FC/PC, SC/PC, ST/PC, etc.
- 1(Simplex) or 2(Duplex)
- Cable material: 1-PVC, 2-PA, 3-Hytrel, etc.
- Cable type: 250 μm, 900 μm, 2.4mm, 3.0mm, etc
- Length: 1m, 2m, 3m, or specified
- SM(Single-mode) or MM(Multimode)
- A: Patchcords, I: Pigtailes

Prime Optical Fiber Corporation

No.11, Ke Jung Rd.
Science-Based Industrial Park
Chu-Nan, 350, Miao-Li County, Taiwan, R.O.C.
Tel: 886-37-586999 Fax: 886-37-586899
E-mail: sales@pofc.com.tw

